

Application No.: 10/760,042

Amendment dated: January 24, 2006

Reply to Office Action of August 23, 2005 and January 20, 2006

Listing of Claims:

- 1 1. (Currently Amended) A movable barrier system comprising, a door jamb, a
2 guide track rearwardly offset from said door jamb to form an open space
3 therebetween, a roller mounted door movable along said guide track between
4 a closed position and an open position, and an elongate shield having a first
5 leg attached to said door jamb laterally outwardly of said guide track and
6 having a second leg extending wherein said shield extends rearward from said
7 door jamb and overlies at least a portion of said guide track to cover said open
8 space, and a tab extending from said second leg and contacting said door
9 jamb at a fulcrum, whereby said shield may be pivotally adjusted to selectively
10 position said first leg angularly inwardly and outwardly relative to said guide
11 track to cover said open space.

- 1 2. (Currently Amended) The movable barrier system of claim 1, wherein the
2 part of said elongate shield overlying said guide track is flexible.

- 1 3. (Currently Amended) A movable barrier system comprising, a door jamb, a
2 guide track rearwardly offset from said door jamb to form an open space
3 therebetween, a roller mounted door movable along said guide track between
4 a closed position and an open position, and an elongate shield attached to
5 said door jamb laterally outwardly of said guide track, wherein said elongate
6 shield extends rearward from said door jamb and overlies at least a portion of
7 said guide track to cover said open space and wherein said elongate shield
8 includes a first leg extending substantially parallel to said door jamb and a
9 second leg extending rearwardly from said first leg, and a tab extending
10 inwardly from said second leg, wherein said tab engages and engaging said
11 guide track.

- 1 4. (Previously Presented) The movable barrier system of claim 3, wherein said
2 tab is flexible.

Application No.: 10/760,042
Amendment dated: January 24, 2006
Reply to Office Action of August 23, 2005 and January 20, 2006

- 1 5. (Previously Presented) The movable barrier system of claim 4, wherein said
2 elongate shield is constructed entirely of metal.
- 1 6. (Previously Presented) The movable barrier system of claim 4, wherein said
2 first leg and said second leg are constructed of metal and said tab is
3 constructed of plastic.
- 1 7. (Previously Presented) The movable barrier system of claim 4, wherein said
2 elongate member is constructed entirely of plastic, said first leg and said
3 second leg being a rigid plastic and said tab being a flexible plastic.
- 1 8. (Previously Presented) The movable barrier system of claim 4 further
2 comprising, a second tab extending forward from the lateral outward
3 extremity of said first leg.
- 1 9. (Previously Presented) The movable barrier system of claim 4, wherein said
2 tab extends rearward as it extends inward from said second leg.
- 1 10. (Previously Presented) The movable barrier system of claim 9, wherein said
2 tab has an increasingly reduced thickness as it extends outward from said
3 second leg.
- 1 11. (Canceled)
- 1 12. (Previously Presented) A door system used in connection with an opening
2 defined by a pair of jambs and a laterally extending header connecting the
3 jambs, the door system comprising, a pair of tracks mountable on the
4 jambs, said tracks having a vertical track section running adjacent the
5 jambs, wherein a space is defined between said tracks and the jambs along

Application No.: 10/760,042

Amendment dated: January 24, 2006

Reply to Office Action of August 23, 2005 and January 20, 2006

6 at least a portion of their length, a door mounted for movement on said
7 tracks and movable between an open position and a closed position, and a
8 shield mounted laterally outward of said tracks and adjacent thereto, said
9 shield extending rearward from the jamb and overlying at least a portion
10 of said tracks along the length of said vertical track section, wherein said
11 overlying portion of said shield contacts said vertical track section along
12 said length thereof, and wherein said shield includes a first leg extending
13 substantially parallel to and attached to the jamb and a second leg
14 extending rearwardly from said first leg, said second leg being spaced
15 laterally outward from said tracks and a tab extending inward from said
16 second leg and contacting said tracks.

1 13. (Original) The door system of claim 12, wherein said tab is flexible.

1 14. (Original) The door system of claim 13, wherein said tab is constructed of
2 a nonmetallic material.

1 15. (Original) The door system of claim 12 further comprising, a second tab
2 extending forward from said first leg, said second tab contacting the jamb
3 at a fulcrum, wherein said first leg is attached to the jamb at a point
4 laterally inwardly of said second tab.

1 16. (Previously Presented) The door system of claim 15, wherein said first leg
2 is attached to the jamb by an adjustable fastener, whereby said first leg may
3 be pivotally adjusted about said fulcrum to provide a variable pressure
4 contact of said tab against said vertical guide section.

1 17. (Previously Presented) The door system of claim 15 further comprising, a
2 mounting bracket attachable to the jamb and said track to support said

Application No.: 10/760,042
Amendment dated: January 24, 2006
Reply to Office Action of August 23, 2005 and January 20, 2006

3 track on the jamb, said first leg of said shield extending laterally outwardly
4 beyond and enclosing said mounting bracket.

1 18. (Original) The door system of claim 17, wherein said mounting bracket is
2 L-shaped with said second tab, said first leg, said second leg and said tab
3 substantially enclosing said bracket.

1 19. (Original) The door system of claim 17, including a plurality of said
2 mounting brackets attaching said vertical track section to said jamb at
3 different distances therefrom with said tab contacting the vertical track
4 section throughout the length thereof.

1 20. (Previously Presented) The door system of claim 12, wherein said shield is
of uniform cross-sectional configuration along its length.

1 21. (Canceled)

1 22. (Canceled)

1 23. (Canceled)

1 24. (Canceled)

1 25. (New) A movable barrier system according to claim 1, wherein said first leg
2 is attached to said door jamb at a point laterally inwardly of said tab by an
3 adjustable fastener.

1 26. (New) The movable barrier system according to claim 25 further
2 comprising, a mounting bracket attaching said guide track to said door

Application No.: 10/760,042

Amendment dated: January 24, 2006

Reply to Office Action of August 23, 2005 and January 20, 2006

- 3 jamb, said first leg of said shield extending laterally outwardly beyond and
4 enclosing said mounting bracket.